Felicitysolar®

Make life full of hope



25~50kW

Hybrid Solar Inverter

IVGM Series | High-voltage | Three Phase



IVGM25K/29K9/30K/40K/50KHP3G2

Features

- AI-powered Forecasting & Personalized Energy Optimization
- Remote Monitoring via Fsolar APP
- Supports Single-phase input, Three-phase Output
- Wide Grid Standard Compatibility
- Time of Use Function
- Max.12 Units in Parallel
- IP65-rated Protection
- User-friendly Touchscreen

Guangzhou Felicity Solar Technology Co.,Ltd.

www.felicitysolar.com sales@felicitysolar.com

No. 2, Donghua Huaye Road, Renhe Town, Baiyun District, Guangzhou, China **(Only 10 Mins from Baiyun International Airport)**

Official Website

Facebook

Model	IVGM50KHP3G2	IVGM40KHP3G2	IVGM30KHP3G2	IVGM29K9HP3G2	IVGM25KHP3G2
Battery Input Data					
Battery Type	LFP (LiFePO4)				
Battery Voltage Range	160~800Vdc				
Max. Charging Current	50+50(A)				
Max. Discharging Current	50+50(A)				
Number of Battery Input	2				
PV String Input Data					
Max. DC Access Power	100kW	80kW	60kW	59.8kW	50kW
Max. DC Input Power	80kW	64kW	48kW	47.84kW	40kW
Max. DC Input Voltage	1000Vdc				
Min. DC Input Voltage	150Vdc				
Start-up Voltage	180Vdc				
Rated DC Input Voltage	600Vdc				
MPPT Range	150~850Vdc				
Full Load DC Voltage Range	550~850Vdc	444~850Vdc	444~850Vdc	443~850Vdc	555~850Vdc
PV Input Current	36+36+36+36(A)		36+36+36(A)		36+36(A)
Max. PV Isc	55+55+55+55(A)		55+55+55(A)		55+55(A)
No.of MPP Trackers	4		3		2
No.of Strings Per MPP Tracker	2		2		2
AC Output Data					
Rated AC Output Power	50kW	40kW	30kW	29.9kW	25kW
Max. AC Output Power	55kW	44kW	33kW	29.9kW	27.5kW
AC Output Rated Current	72.5A	58A	43.5A	43.4A	36.3A
Max. AC Current	79.7A	63.8A	47.9A	43.4A	39.9A
Rated AC Voltage	220/380, 230/400 Vac (-20%~+15%)				
AC Wiring Mode	3L+N+PE				
Rated AC Frequency	50 /60 Hz (45~55Hz/55~65Hz)				
THDI	<3% (At Rated Power)				
Power Factor	0.8(Leading) to 0.8(Lagging)				
Safety and Standards					
Surge Protection Level	TYPE II(DC), TYPE II(AC)				
Over Voltage Category	OVCII (DC), OVC III (AC)				
Grid Regulation	NRS 097-2-1, VDE4105, EN50549-1, AS 4777.2, GB/T 34120, GB/T 34133, GB/T 34129				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
Protection					
PV Input Lightning Protection	Integrated				
PV String Input Reverse Polarity Protection	Integrated				
Battery Input Lightning Protection	Integrated				
AC Output Lightning Protection	Integrated				
Battery Input Reverse Polarity Protection	Integrated				
Insulation Resistor Detection	Integrated				
Residual Current Monitoring Unit	Integrated				
Output Over Current Protection	Integrated				
Output Short-Circuit Protection	Integrated				
Output Over Voltage Protection	Integrated				
Anti-islanding Protection	Integrated				
General Data					
Net Weight	87.1KG		80KG		
Gross Weight	107.1KG		101KG		
Product Dimension	940*582*340MM				
Package Dimension	1114*774*469MM				
Protection Degree	IP65				
Operating Temperature Range	-40 to 60 (> 50 Derating)				
Humidity	0~ 95 % (No Condensation)				
Cooling	Smart Cooling				
Communication with BMS	RS485,CAN				
Monitor Module	WiFi/GPRS				
Installation Style	Wall-mounted				
Warranty	10 Years				

*Refer to Felicitysolar's Warranty Policy for applicable conditions.

Guangzhou Felicity Solar Technology Co.,Ltd.

www.felicitysolar.com sales@felicitysolar.com

No. 2, Donghua Huaye Road, Renhe Town, Baiyun District, Guangzhou, China **(Only 10 Mins from Baiyun International Airport)**

Official Website

Facebook