


Safety Data Sheet

Chemical product and company identification	
Sample Name	Lithium Iron Phosphate Battery
Model	LUX-Y-48100HG01M4 LUX-Y-48100HG01M5 LUX-Y-48100HG01M6 LUX-Y-48100HG01M7 LUX-Y-48100HG01M8 LUX-Y-48100HG01M9 LUX-Y-48100HG01M10 LUX-Y-48100HG01M11 LUX-Y-48100HG01M12
Manufacture	Guangdong Felicity New Energy Co., Ltd.
Manufacture Address	(KongGangBaiYun)No. 2, Donghua Huaye Road, Renhe Town, Baiyun Area Guangzhou Guangdong, P.R. China
Australian Importer	FELICITY SOLAR AUSTRALIA PTY LTD
Australian Importer Address	706 160 GOULBURN STSURREY HILLS NSW 2010 service@felicityess.com
Emergency telephone call	+61 0412862116
Hazards Identification	
Hazard label	 <p>No.9A hazard label</p>
Explosive risk	This article does not belong to the explosion dangerous goods.
Flammable risk	This article does not belong to the flammable material.
Oxidation risk	This article does not belong to the oxidation of dangerous goods.
Toxic risk	This article does not belong to the toxic dangerous goods.
Radioactive risk	This article does not belong to the radiation of dangerous goods.
Mordant risk	This article does not belong to the corrosion of dangerous goods.
other risk	Battery which belong to the Lithium-ion battery.

Composition information			
Hazardous components	Content /wt%	CAS No.	EC No.
LiFePO ₄	38.8	15365-14-7	--
C	19.4	7782-42-5	--
(C ₂ H ₄) _n	2.2	9002-88-4	--
Al	4.2	7429-90-5	--
Cu	6.7	7440-50-8	--
Al	7.2	7429-90-5	--
(C ₈ H ₈ .C ₄ H ₆) _n	0.8	9003-55-8	--
C	0.4	1333-86-4	--
C ₂ H ₂ F ₂	0.8	24937-79-9	--
LiPF ₆	2.3	21324-40-3	--
C ₃ H ₄ O ₃	5.6	96-49-1	--
C ₄ H ₈ O ₃	4.6	623-53-0	--
C ₃ H ₆ O ₃	5.6	616-38-6	--
Adhesive	1.4	--	--
First aid measures			
Eye: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid. Skin: Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid. Inhalation: Remove from exposure and move to fresh air immediately. Use oxygen if available. Ingestion: Give at least 2 glasses of milk or water. Go to the hospital immediately for medical treatment.			
Fire-fighting measures			
Flash Point: N/A. Auto-Ignition Temperature: N/A. Extinguishing Media: Water, CO ₂ . Special Fire-Fighting Procedures: Self-contained breathing apparatus. Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heat-exposing battery contents. Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.			

Accidental release measures
<p>Steps to be Taken in case Material is Released or Spilled</p> <p>If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.</p> <p>Waste Disposal Method</p> <p>It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.</p>
Handling and storage
<p>The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.</p> <p>Precautions to be taken in handling and storing</p> <p>Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.</p> <p>Other Precautions</p> <p>The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.</p>
Exposure controls/personal protection
<p>Respiratory Protection</p> <p>In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.</p> <p>Ventilation</p> <p>Not necessary under conditions of normal use.</p> <p>Protective Gloves</p> <p>Not necessary under conditions of normal use.</p> <p>Other Protective Clothing or Equipment</p> <p>Not necessary under conditions of normal use.</p> <p>Personal Protection is recommended for venting battery</p> <p>Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.</p>

Physical and chemical properties
<p>Appearance: Quadrate shape.</p> <p>Odors: If leaking, smells of medical ether.</p> <p>pH: Not applicable as supplied.</p> <p>Flash Point: Not applicable unless individual components exposed.</p> <p>Flammability: Not applicable unless individual components exposed.</p> <p>Relative density: Not applicable unless individual components exposed.</p> <p>Solubility (water): Not applicable unless individual components exposed.</p> <p>Solubility (other): Not applicable unless individual components exposed.</p>
Stability and reactivity
<p>Stability: Product is stable under conditions described in Section 7.</p> <p>Conditions to Avoid: Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.</p> <p>Materials to avoid: Oxidising agents, alkalis, water.</p> <p>Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.</p> <p>Hazardous Polymerization: N/A.</p> <p>If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated Hydrocarbons.</p>
Toxicological information
<p>Signs & symptoms: None, unless battery ruptures.</p> <p>In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.</p> <p>Inhalation: Lung irritant</p> <p>Skin contact: Skin irritant.</p> <p>Eye contact: Eye irritant.</p> <p>Ingestion: Poisoning if swallowed.</p> <p>Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target Organs nerves, liver and kidneys.</p>
Ecological information
<p>Mammalian effects: None known at present.</p> <p>Eco-toxicity: None known at present.</p> <p>Bioaccumulation potential: Slowly Bio-degradable.</p> <p>Environmental fate: None known environmental hazards at present.</p>
Disposal consideration
<p>Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in</p>



Guangdong Felicity New Energy Co., Ltd

Address:(Airport Baiyun)No.2, 4, 6, 8, 10 and 12 Donghua Huaye Road, Renhe Town, Baiyun District, Guangzhou, Guangdong, P. R. China

loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

Transport information

Label for conveyance: No.9A hazard label
UN Number: UN 3480
Proper Shipping name: Lithium ion batteries
IMDG Code/TDG Special provisions: 230, 310, 348, 376, 377, 384, 387
IMDG Code/TDG Packing Instruction: P903
EmS No: F-A ,S-I
Marine pollutant: No
Hazard Classification: The goods shall be complied with the requirements of the Packing Instructions TDG 23th Edition and the Packing Instructions P903 of IMDG Code (Amdt.42-24), including the passing of the UN38.3 test.

Regulation information

The laws and regulations applicable to the transportation of lithium batteries are as follows:
The UN Model Regulations, United Nations ST/SG/AC.10/1/Rev 23. Recommendations on the Safe Transport of Dangerous Goods
The International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air Transport
The International Air Transport Association (IATA) Dangerous Goods Regulations (66th Edition 2025)
International Maritime Organization (IMO) International Maritime Dangerous Goods Code (IMDG Code) (Amdt.42-24)
Agreement concerning the International Carriage of Dangerous Goods by Road (ADR 2025)
JT/T 617-2018 Regulations concerning road transportation of dangerous goods.

Other information

This file is only effective to the batteries
(Model:LUX-Y-48100HG01M4,LUX-Y-48100HG01M5,LUX-Y-48100HG01M6,LUX-Y-48100HG01M7,LUX-Y-48100HG01M8,LUX-Y-48100HG01M9,LUX-Y-48100HG01M10,LUX-Y-48100HG01M11,LUX-Y-48100HG01M12) provided by commissioner which manufactured by Guangdong Felicity New Energy Co., Ltd. The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER doesn't assume responsibility for any damage or loss because of misuse of batteries.